

KT-M24

23.8" FHD Monitor

Design and specifications are subject to change without notice. Pictures in the document are for reference only, and the actual product shall prevail.



Features :

- Light and cost-effective plastic housing;
- Ultra-narrow bezel , elegant appearance, metal base;
- 178°H/178°V extra-wide viewing angle for overall viewing performance;
- High fidelity digital processing for a brilliant and vivid video;
- Support multiple signal inputs such as HDMI, VGA;
- Physical button control mode;
- Low energy consumption, long service life;
- Anti-blue light design, eye-protective.



Technical Specification

Model

Model KT-M24

Display

| | |
|----------------------|------------------------------|
| Screen Size | 23.8" |
| Panel type | VA |
| Aspect Ratio | 16:9 |
| Resolution | 1920×1080 (FHD) |
| Backlight | LED |
| Brightness/Luminance | 250 cd/ m ² (max) |
| Contrast | 4000:1 |
| Display Color | 16.7M(8bit) |
| Viewing Angle(H/V) | 178°(H)/178°(V) |
| Response time | 6ms (max) |
| Refresh Rate | 100Hz (max) |

Signals

| | |
|--------|---------------|
| Input | VGA×1, HDMI×1 |
| Output | NO |

Speaker

Speaker NO

General

| | | |
|---------------------------------|-------------------------------------|-----------------------|
| Power Supply | DC 12V | |
| Consumption (Standard) | 25W | |
| Consumption (Standby) | ≤0.5W | |
| Net Weight | 2.87kg (6.32lb) | |
| Gross Weight | 3.82kg (8.41lb) | |
| Bezel Width | 2.1mm(U/R/L) 15.9mm(B) | |
| Wall Mount | 75x75mm (3.0"x3.0") | |
| Dimension without stand (W×H×D) | 539.2x320.4x41.3mm(21.2"x13"x1.62") | |
| Package(W×H×D) | 612x101x405mm (24.1"x4.0"x16.0") | |
| Work Environment | Temperature | 0°C~40°C (32°F~104°F) |
| | Humidity | 10%~85% |

Accessory

Standard HDMI cable, Adapter, base

KT-M24

23.8" FHD Monitor

Design and specifications are subject to change without notice. Pictures in the document are for reference only, and the actual product shall prevail.

Dimensions

