


# KX-CSW24-PFL2

## 26-Port Unmanaged Desktop Switch with 24-Port PoE

Design and specifications are subject to change without notice. Pictures in the document are for reference only, and the actual product shall prevail.



- 24 × RJ-45 10/100 Mbps (PoE) ports, 2 × RJ-45 10/100/1000 Mbps (combo) ports and 2 × SFP 1000 Mbps (combo) ports.
- Meets the requirements of IEEE802.3af, IEEE802.3at, Hi-PoE, and IEEE802.3bt power supply standards.
- PoE watchdog real-time monitors camera statuses and automatically reboots faulty network cameras.
- Up to 250 m transmission distance.
- Supports VIP ports, prioritizing transmission for port1 to port8.



### Specification

#### Hardware Feature

Included Power Adapter	Yes
PoE	Yes
Ethernet Port	24
Ethernet Port Speed	10/100 Mbps
Ethernet Port Uplink Speed	10/100/1000 Mbps
Optical Port Uplink Speed	1 Gbps
Description of Function Slots	Port 1-24: 24 × RJ-45 10/100 Mbps; Port 25-26: 2 × RJ-45 10/100/1000 Mbps (Combo); Port 25-26: 2 × SFP 1000 Mbps (Combo)
Power Supply	Built-in power supply: 100-240 VAC, 50/60 Hz, 4 A
Operating Temperature	-10 °C to +55 °C (+14 °F to +131 °F)
Operating Humidity	5%–95% (RH), non-condensing
Storage Temperature	-40 °C to +75 °C (-40 °F to +167 °F)
Storage Humidity	5%–95% (RH), non-condensing
Power Consumption	Idling: ≤8.5 W ; Full load: 265 W

#### Performance

Management Type	No
Switching Capacity	8.8 Gbps
Packet Forwarding Rate	6.55 Mpps
Packet Buffer Size	4 Mbit
Jumbo Frame	15K Byte
MAC Table Size	8 K
Communication Standard	IEEE802.3; IEEE802.3u; IEEE802.3x; IEEE802.3ab; IEEE802.3z

### Feature

PoE Protocol	IEEE802.3af; IEEE802.3at; Hi-PoE; IEEE802.3bt
PoE Power	Port 1-2 ≤ 90 W, Port 3-24 ≤ 30 W, total ≤ 240 W
PoE Pin Assignment	1,2,4,5 (V+), 3,6,7,8 (V-)
Long Distance PoE Transmission	Yes

### General

Statics Protection	Air discharge: 8 kV; Contact discharge: 6 kV
Lighting Protection	Common mode: 4 kV; Differential mode: 2 kV
Net Weight	2.47 kg (5.45 lb)
Gross Weight	3.12 kg (6.88 lb)
Product Dimensions	440 mm × 220 mm × 44 mm (17.32" × 8.66" × 1.73") (L × W × H)
Packaging Dimensions	540 mm × 342 mm × 90 mm (21.26" × 13.46" × 3.54") (L × W × H)
Casing Material	Sheet metal
Installation	Desktop mount; DIN-Rail mount

## KX-CSW24-PFL2

26-Port Unmanaged Desktop Switch with 24-Port PoE

Design and specifications are subject to change without notice. Pictures in the document are for reference only, and the actual product shall prevail.

### Transmission Performance:

Switch power supply voltage 53V.  
CAT5E/CAT6. Max. DC resistance < 10 Ω/100 m

Cable(m)	Load Capacity(W)	Bandwidth(Mbps)
----------	------------------	-----------------

IEEE802.3bt 90 W

100	71.3	100
150	62	10
200	51	10
250	40	10

Hi-PoE 60 W

100	53	100
150	50	10
200	47	10
250	37	10

IEEE802.3at 30 W

100	25.5	100
150	25.5	10
200	25.5	10
250	25.5	10

### Dimensions (mm[inch])

