

KX-ADA2111ZCN3

2 MP Lite Fixed-Focal Bullet Network Camera

Design and specifications are subject to change without notice. Pictures in the document are for reference only, and the actual product shall prevail.



- 2-MP 1/2.8" CMOS image sensor, low illuminance, high image definition.
- Outputs max. 2 MP (1920 × 1080) @25/30 fps.
- H.265 codec, high compression rate, ultra-low bit rate.
- Built-in efficient IR illuminator, and the max. illumination distance is 30 m.
- ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments.
- Rotation mode, DWDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes.
- Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, and illegal access.
- 12 VDC/PoE power supply.
- IP67 protection.



Technical Specification

Camera

| | |
|----------------------------|---|
| Image Sensor | 1/2.8" CMOS |
| Max. Resolution | 1920 (H) × 1080 (V) |
| ROM | 16 MB |
| RAM | 64 MB |
| Scanning System | Progressive |
| Electronic Shutter Speed | Auto/Manual 1/3 s–1/100,000 s |
| Min. Illumination | 0.01 lux@F2.0 (Color,30 IRE) 0.001 lux@F2.0 (B/W,30 IRE) 0 lux (Illuminator on) |
| S/N Ratio | > 56 dB |
| Illumination Distance | Up to 30 m (98.4 ft) (IR) |
| Illuminator On/Off Control | Auto; manual |
| Illuminator Number | 2 (IR LED) |
| Pan/Tilt/Rotation Range | Pan: 0°–360° Tilt: 0°–90° Rotation: 0°–360° |

Lens

| | |
|---------------|--|
| Lens Type | Fixed-focal |
| Lens Mount | M12 |
| Focal Length | 3.6 mm |
| Max. Aperture | 3.6 mm: F2.0 |
| Field of View | 3.6 mm: Horizontal: 84°; Vertical: 45°; Diagonal: 100° |

| | | | | | |
|----------------------|------------------------|-------------------|------------------|-----------------|-----------------|
| Iris Control | Fixed | | | | |
| Close Focus Distance | 3.6 mm: 0.8 m (2.6 ft) | | | | |
| DORI Distance | Lens | Detect | Observe | Recognize | Identify |
| | 3.6 mm | 49.7 m (163.1 ft) | 19.9 m (65.3 ft) | 9.9 m (32.5 ft) | 5.0 m (16.4 ft) |

Video

| | |
|-------------------|---|
| Video Compression | H.265; H.264; H.264B; 264H; MJPEG (Only supported by the sub stream) |
| Smart Codec | Smart H.265+; Smart H.264+ |
| Video Frame Rate | Main stream: 1920 × 1080@1–25/30 fps Sub stream: 704 × 576@1–25 fps 704 × 480@1–30 fps *The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity. |
| Stream Capability | 2 streams |
| Resolution | 1080p (1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF (352 × 288/352 × 240) |
| Bit Rate Control | CBR/VBR |
| Video Bit Rate | H.264: 32 kbps–6144 kbps H.265: 12 kbps–6144 kbps |
| Day/Night | Auto (ICR)/Color/B/W |
| BLC | Yes |
| HLC | Yes |
| WDR | DWDR |

KX-ADA2111ZCN3

2 MP Lite Fixed-Focal Bullet Network Camera

Design and specifications are subject to change without notice. Pictures in the document are for reference only, and the actual product shall prevail.

| | |
|--------------------------|---|
| White Balance | Auto; natural; street lamp; outdoor; manual; regional custom |
| Gain Control | Manual; auto |
| Noise Reduction | 3D NR |
| Motion Detection | OFF/ON (4 areas, rectangular) |
| Region of Interest (RoI) | Yes (4 areas) |
| Smart Illumination | Yes |
| Image Rotation | 0°/90°/180°/270° (Support 90°/270° with 1080p resolution and lower) |
| Mirror | Yes |
| Privacy Masking | 4 areas |
| Alarm | |
| Alarm Event | Network disconnection; IP conflict; illegal access; motion detection; video tampering; security exception |
| Network | |
| Network Port | RJ-45 (10/100 Base-T) |
| SDK and API | Yes |
| Cyber Security | Video encryption; Configuration encryption; Digest; WSSE; Account lockout; Security logs; Generation and importing of X.509 certification; Trusted boot; Trusted execution; Trusted upgrade |
| Network Protocol | IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; SMTP; FTP; DHCP; DNS; DDNS; NTP; Multicast; ICMP; IGMP |
| Interoperability | ONVIF(Profile S); CGI; P2P |
| User/Host | 6 (Total bandwidth: 36 M) |
| Storage | FTP |
| Browser | IE; Chrome; Firefox |
| Mobile Client | iOS; Android |
| Power | |
| Power Supply | 12 VDC/PoE (802.3af) |
| Power Consumption | Basic power consumption: 1.3 W (12 VDC); 2.1 W (PoE) Max. power consumption (ICR + H.265+IR intensity): 2.9 W (12 VDC); 3.9 W (PoE) |
| Environment | |
| Operating Temperature | -40 °C to +55 °C (-40 °F to +131 °F) |
| Operating Humidity | ≤ 95% |
| Storage Temperature | -40 °C to +60 °C (-40 °F to +140 °F) |
| Protection | IP67 |

Structure

| | |
|--------------------|---|
| Casing | plastic |
| Product Dimensions | 198.9 mm × 80.2 mm × 76.2 mm (7.83" × 3.16" × 3.00") (L × W × H) |
| Net Weight | 0.25 kg (0.55 lb) |
| Gross Weight | 0.40 kg (0.88 lb) |

Dimensions (mm[inch])

